



DURATEXT

Acrylic emulsion based, photocatalytic roller or spray applied, patternable, construction last layer grainy exterior facade cladding.

PROPERTIES

DURATEXT It is capable of breathing.

The pores in the acrylic silicone structure have been treated It doesn't spill because the humidity in the wall is prevented from being thrown out. Rain resistant to water, water repellent properties remains dry continuously. Photocatalytic special- It has a lattice. It has high covering power.

APPLICATION SURFACES

Plaster, concrete, gross concrete, cement board, MDF, OSB, color-lost self- old painted surfaces-appl cable.

APPLICATION

The surface must be dry and clean. There must not be any waste. After pouring the concrete to wait for the setting time (28 days full curing) If necessary, Repairs and repairs must be carried out. Especially on concrete surfaces high porosity these surfaces must be gun with putty and liner. Surface before coating process Primed with Durapaint primer. Duratext can be applied by spraying.

Under Shine is not recommended. Shadow application on the facades It is recommended. Standard pattern fasten and abrupt water of material specified for the prevention of loss these necessary conditions must be met.

CONSTRUCTION TECHNICAL

Specification 'What is appropriate Application on building surfaces is required.

DRYING TIME

(20 ° C, 65% HR)

Touch dry: 30-45 minutes

Final drying: 24 hours.

THINNING

Ready to use.

CONSUMPTION

According to the pattern area between 1.3 - 2.3 m2 with 1 kg.

SHELF LIFE

- In unopened package,
- Cool and dry place from frost, direct sunlight can be stored for 24 months.
- After using cover of the packaging.